

Zhengzhou Crown Import And Export Trading Co.,ltd. TEL:008613503831890(China) 00919825073543(India) Email:lulu19870907@hotmail.com parasinternational47@gmail.com Web:www.parasinternational.co.in

Add:Floor No.1, Courtyard No.87, Jinhai Road, Erqi District, Zhengzhou City, China

亚克力A9300 超工程级反光膜(国II)

国标Ⅱ类反光膜 质保7-10年

产品简介

A9300亚克力超工程级反光膜(国II)是一款符合国标《GB/T 18833-2012道路交通反光膜》中II类反光膜各项性能要求的产品。可应用于永久性交通标志、作业区交通设施、各类车辆的反光标识贴等领域,保障道路和车辆人员安全。



产品图

产品型号



白色



黃色





橙色.



蓝色





亚克力07 棕色

颜	色	白色	黄色	红色	橙色	蓝色	绿色	棕色				
逆反射 ^{単位:cd}		250	175	50	100	20	45	12				
使用年	丰限		户外耐候7~10年									
适用》	温度		寒耐热)°C~70°		施工温度: 10℃~36℃							
厚度家	克重	厚度	:>0.4r	nm	克重: >400g/㎡							
规	格		品规格 *45.7m	/R	外箱规格 1280*220*240mm							
特	性	国标Ⅱ	类反光原	漠、耐候	7~10年	、适用疗	k久性交	通标识				
加工二	L艺	UV喷绘、丝网印刷、刻字										
适用落	 包围	永久性	交通标志	标牌、作	业区交通	通设施、车	 F辆反光	示识等				





产品应用图



3500

高亮平面喷绘反光膜

BRIGHT PLANE SPRAY REFLECTIVE FILM










产品简介 PRODUCT INTRODUCTION

高亮平面喷绘反光膜,是一款高反光亮度的反光喷绘膜。相较于传统晶 彩格反光膜,本产品具有更高、更均匀的反光亮度,因而在交通领域的应 用更具优势。此外,产品还可进行喷绘、写真、印刷等工艺加工,应用于临 时施工标牌、临时交通标识、车辆反光警示标识、户外广告喷绘等领域。

The bright plane spray reflective film is a reflective spray film with high reflective brightness. Compared with the traditional crystal color lattice reflective film, this product has higher and more uniform reflective brightness, so it has more advantages in the application of transportation. In addition, the products can also be processed by painting, photo, printing and other processes, and are applied to temporary construction signs, temporary traffic signs, vehicle reflective warning signs, outdoor advertising painting



颜色	白色	红色	蓝色	绿色	黄色	橙色	偏黄	
逆反射系数 ^{单位:cd/lx/m²}	250	50	20	45	175	100	175	
使用年限			户外	耐候13	Ŧ			
适用温度	-	耐寒耐 10℃~			施工温度: 10℃~36℃			
厚度克重		厚度:>	38C		克重: >380g/m²			
产品规格			50n	n*1.24r	m/R			
特性		高亮均	自匀、表	長观平豊	を、无接	發线		
加工工艺			喷绘、	写真、	印刷			
适用范围			示牌、 户外广			、车辆。	反光	

Color	White	Red	Blue	Gre	en	Yellow	Orange	Yellowish	
Reflection coefficient unit:cd/lx/m²	250	50	20	4	5	175	100	175	
Service life	Outdoor Weatherproof for 1 years								
Applicable temperature	Cold and Heat Resistance: -10℃~60℃				Coi	Construction Temperature: 10°C~36°C			
Thickness weight	Thickness: >38c				Gram weight: 380g/m²				
Product Specification			50	m*1.	24n	n/R			
Characteristic						rm, the		nce	
Processing technology		Sp	ray pain	ting,	pho	to, print	ing		
Scope of application	signs	, vehicle		e wa	rnin	tempora g signs,			



V3800

无缝条形PET反光膜(EGP高亮型)

SEAMLESS STRIP PET REFLECTIVE FILM (EGP HIGHLIGHT TYPE)









产品简介PRODUCTINTRODUCTION

无缝条形 PET 反光膜 (高亮型),是一款高亮均匀的无缝 PET 印刷反光 膜。具有反光亮度更高更均匀、膜面没有接缝线且更透亮美观、可进行 UV 打印加工等特点。产品可进行刻字雕刻、丝网印刷、UV 打印等工艺加 工,应用于临时性交通设施、警示牌、临时性交通告示牌、车辆反光警示 标识等领域。

Seamless strip pet reflective film (high brightness type) is a seamless pet printed reflective film with uniform brightness. It has the characteristics of higher and more uniform reflective brightness, no seam line on the film surface, more transparent and beautiful, UV printing processing, etc. The products can be processed by engraving, screen printing, UV printing and other processes, and can be used in the fields of temporary traffic facilities, warning signs, temporary traffic signs, vehicle reflective warning



无缝条形PET反光膜(EGP高亮型)vs普通晶彩格产品实拍

颜色	白色	红色	蓝色	绿色	黄色	橙色	偏黄			
逆反射系数 ^{单位:cd/lx/m²}	250	50	20	45	175	100	175			
使用年限		户外耐候1~3年								
适用温度	_	耐寒耐 10℃~			施工温度: 10℃~36℃					
厚度克重		厚度:>	45C		克重: >490g/㎡					
产品规格			45.7	m*1.22	?m/R					
特性		高亮	均匀、	无缝美	观、UV	/打印				
加工工艺	雕刻、丝印									
适用范围			通设施、 所反光警			対性交	通告			

	White	Red	Blue	Gre	en	Yellow	Orange	Yellowish
Reflection coefficient unit:cd/lx/m²	250	50	20	4	5	175	100	175
	Outdoor Weatherproof for 1~3 years							
Applicable temperature	Cold and Heat Resistance: -10℃~60℃				Construction Temperature: 10℃~36℃			
	Thickness: >45c				Gram weight: 490g/m²			
Product Specification			45	.7m*	1.22	2m/R		
	Unifor	m highlig	ght, sean	nless	and	d beautif	ul, UV pr	inting
Processing technology		En	graving	and :	silk :	screen p	rinting	
Scope of application	const	ruction s		npor	ary	nting, ten traffic si		icle



J7300

无缝条形PET反光膜(经济型)

SEAMLESS STRIP PET REFLECTIVE FILM (ECONOMICAL)









产品简介PRODUCTINTRODUCTION

无缝条形 PET 反光膜(经济型),是一款无拼接线的 PET 反光膜。具有无 接缝线、经济实惠、材质柔软易于刻字等特点。产品可进行刻字雕刻、丝 网印刷等工艺加工,应用于临时性交通设施、警示牌、临时性交通告示 牌、车辆反光警示标识等领域。

Seamless strip pet reflective film (economical type) is a pet reflective film without splicing. It has the characteristics of no suture, economic benefit, soft material and easy lettering. The products can be processed by engraving, screen printing and other processes, and can be used in the fields of temporary traffic facilities, warning signs, temporary traffic signs, vehicle reflective warning signs and so on.



产品反光效果实拍

颜色	白色	红色	蓝色	绿1	色	黄色	橙色	偏黄		
逆反射系数 ^{单位:cd/lx/m²}	140	30	10	30	Э	80	60	80		
使用年限			户外	耐候	₹1~	·3年				
适用温度	-	耐寒耐热: -10℃~60℃					施工温度: 10℃~36℃			
厚度克重	厚度:>40C					克重: >375g/m²				
产品规格			45.7	m*1	.22	?m/R				
特性		无接	缝线、	经济	突	惠、材	质柔软			
加工工艺	雕刻、丝印									
适用范围			通设施、 列反光警				时性交	通告		

	White	Red	Blue	Gre	en	Yellow	Orange	Yellowish
Reflection coefficient unit:cd/lx/m²	140	30	10	3	0	80	60	80
	Outdoor Weatherproof for 1~3 years							
Applicable temperature	Cold and Heat Resistance: -10°C~60°C				Construction Temperature: 10°C~36°C			
	Th	ickness:	>40c		Gram weight: 375g/m²			
Product Specification			45.	7m*	1.22	m/R		
		No sear	m, econo	mica	al ar	nd soft m	naterial	
Processing technology	Engraving and silk screen printing							
Scope of application						rning sig signs of		



闪亮星反光膜

SHINING STAR REFLECTIVE FILM









产品简介PRODUCTINTRODUCTION

闪亮星反光膜,是一款具有反光效果的喷绘膜。产品表面的闪亮晶格设 计, 具有多角度反光、经济实惠、吸墨性能稳定等特点, 可进行喷绘、写 真、印刷等工艺加工,应用于户外广告喷绘、临时施工标牌、临时交通标 识、车辆反光警示标识等领域。

Shiny star reflective film is a spray-painted film with reflective effect. The shiny lattice design on the surface of the product has the characteristics of multi angle reflection, economic benefits, stable ink absorption performance and so on. It can be processed by painting, photo, printing and other processes, and can be used in outdoor advertising painting, temporary construction signs, temporary traffic signs, vehicle reflective warning signs and other fields.



产品反光效果实拍

颜色	白色	红色	蓝色	绿色	黄色	偏黄				
逆反射系数 ^{单位:cd/lx/m²}	150	40	20	30	100	80				
使用年限		户外耐候1年								
适用温度		対寒耐热 0℃~60		施工温度: 10℃~36℃						
厚度克重	<u> </u>	厚度:>35	С	克重: >320g/m²						
产品规格			50m*1.	.24m/R						
特性		反光闪:	亮、吸墨	稳定、为	发货及时					
加工工艺	喷绘、写真、印刷									
适用范围			会、临时 5光警示相		牌、临时	一 寸交通				

	White	Red	Blue	Green	Yellow	Yellowish	
Reflection coefficient unit:cd/lx/m²	150	40	20	30	100	80	
	Outdoor Weatherproof for 1 years						
Applicable temperature	Cold and Heat Resistance: -10°C~60°C			Construction Temperature: 10°C~36°C			
	Thickness: >35c			Gram weight: 320g/m²			
Product Specification			50m*1	.24m/R			
		ny reflecti ely deliver		ink absor	ption and		
Processing technology	Spray painting, photo, printing						
	constru		ns, tempoi	painting, rary traffic tc			



有缝条形晶彩格反光膜

SLIT STRIP CRYSTAL COLOR LATTICE REFLECTIVE FILM









产品简介 PRODUCT INTRODUCTION

有缝条形晶彩格反光膜,是一款具有反光效果的喷绘膜。产品采用了经 典的阴阳条纹设计, 具有经济实惠、吸墨性能稳定等特点, 可进行喷绘、 写真、印刷等工艺加工,应用于户外广告喷绘、临时施工标牌、临时交通 标识、车辆反光警示标识等领域。

The slit strip crystal color lattice reflective film is a spray painting film with reflective effect. The product adopts the classic yin-yang stripe design, which has the characteristics of economic benefits, stable ink absorption performance and so on. It can be processed by inkjet, photo, printing and other processes, and can be used in outdoor advertising inkjet, temporary construction signs, temporary traffic signs, vehicle reflective warning signs and other fields.



产品反光效果实拍

颜色	白色	红色	蓝色	绿色	黄色	偏黄		
逆反射系数 ^{单位:cd/lx/m²}	150	40	20	30	100	80		
使用年限	户外耐候1年							
适用温度		対寒耐热 0℃~60		施工温度: 10℃~36℃				
厚度克重	<u></u>	厚度:>31	С	克重: >310g/m²				
产品规格			45.7m*1	.22m/R				
特性		经济实	惠、吸量	■稳定、.	发货及时	ţ		
加工工艺	喷绘、写真、印刷							
适用范围			会、临时 5光警示	施工标员	牌、临时	交通		

	White	Red	Blue	Green	Yellow	Yellowish	
Reflection coefficient unit:cd/lx/m²	150	40	20	30	100	80	
Service life	Outdoor Weatherproof for 1 years						
Applicable temperature	Cold and Heat Resistance: -10°C~60°C			Construction Temperature: 10°C~36°C			
Thickness weight	Thickness: >31c			Gram weight: 310g/m²			
Product Specification			45.7m*	*1.22m/R			
		atch resis od ink abs		iform high	light and		
Processing technology	Spray painting, photo, printing						
Scope of application	constru		ns, tempoi	rary traffic	temporary s signs, ve		